



Europäisches Patentamt
European Patent Office
Office européen des brevets



Publication number : 0 568 477 A3

12

EUROPEAN PATENT APPLICATION

(21) Application number : 93480030.1

(51) Int. Cl.⁵ : H04L 12/56 L

(22) Date of filing : 23.03.93

(30) Priority : 28.04.92 US 874917

(43) Date of publication of application :
03.11.93 Bulletin 93/44

(84) Designated Contracting States :
DE FR GB

(88) Date of deferred publication of search report :
21.12.94 Bulletin 94/51

(71) Applicant : International Business Machines
Corporation
Old Orchard Road
Armonk, N.Y. 10504 (US)

(72) Inventor : Ahmadi, Hamid
156 Mitchell Road
Somers, New York 10589 (US)


Inventor : Chen, Jeane Shu-Chun
91 North State Rd.
Briarcliff Manor, N.Y. 10510 (US)
Inventor : Chow, Chee-Seng
26 Prospect Avenue
Ossining, New York 10562 (US)
Inventor : Guerin, Roch
Rochambeau Dr.,
Scenic View No. 4
Yorktown Heights, New York 10598 (US)
Inventor : Gun, Levent
4324 Swarthmore Road
Durham, North Carolina 27707 (US)
Inventor : Lee, Anthony Mangchuen
11 Lake St., Apt 2B
White Plains, N.Y. 10603 (US)
Inventor : Tedijanto, Theodore E.
106 Tasman Court
Cary, North Carolina 27513 (US)

(74) Representative : de Pena, Alain
Compagnie IBM France
Département de Propriété Intellectuelle
F-06610 La Gaude (FR)

(54) Method and apparatus for optimum path selection in packet transmission networks.

(57) A packet communications system utilizes a route determining mechanism by identifying principal paths between the source and the destination in the system. Principal paths are minimum hop count paths with a transmission delay less than a specified threshold. Principal path links are accepted as legs of the optimum path, if feasible, i.e., if the resulting load on the link is less than a specified principal threshold. Secondary links are accepted only if the resulting load on the link is less than a specified secondary threshold, where the secondary threshold is less than the principal threshold. All paths must also have a transmission delay less than a specified threshold. Each request for a route includes the source node, the destination node, the load required, the maximum transmission delay and, if desired, the quality of service parameters which all of the legs of the route must satisfy. A modified Bellman-Ford breadth-first search algorithm is used to identify the principal links and, using these principal link identifications, determining the optimum path.

FIG. 5
PATH DETERMINATION PROCEDURE



EP 0 568 477 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 93 48 0030

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cls)
X	EP-A-0 398 614 (BRITISH TELECOMMUNICATIONS) 22 November 1990 * abstract; figure 1 * * page 11, line 24 - page 12, line 10 *	1,6,11	H04L12/56
A	PROCEEDINGS OF THE JOINT CONFERENCE OF THE IEEE COMPUTER AND COMMUNICATIONS SOCIETIES (IEEE INFOCOM '91), vol.3, 7 April 1991, BAL HARBOUR, US pages 1206 - 1213, XP223448 AWERBUCH, B. ET AL. 'Approximate Distributed Bellman-Ford Algorithm' * the whole document *	2,7,12	
A	EP-A-0 215 463 (HITACHI,LTD.) 25 March 1987 * abstract; figure 5 *	3,8,13	
A	US-A-5 081 620 (GIRARD ET AL.) 14 January 1992 * abstract *	4,9,14	
			TECHNICAL FIELDS SEARCHED (Int.Cl.5)
			H04L
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 27 October 1994	Examiner Revellio, H.S.
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application I : document cited for other reasons A : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 (1.12) (P04/CO)